



DATASHEET

DSG40



Technical Specifications

GENERATOR	Prime	kVA	40
		kW	32
	Standby	kVA	44
		kW	35
	Current	A	57
	Power Factor	Cos-φ	0,8
	Frequency	Hz	50
	Voltage	V	400
	N° Phases		3+N
	Rotation Speed	RPM	1500
	Weight	Kg	1000
	Dimensions	L mm	2200
		W mm	900
		H mm	1375
ENGINE	Noise Level	dBA@7mt	67
	Battery	Ah	100
	Battery Voltage	Vcc	12
	Tank Capacity	L	70
	Brand		Perkins
	Model		404J-E22TA
	Emission		Stage V
	N° Cylinders		4
	Displacement	cm ³	2200
	Rotation Speed		1500
	Engine Type		TBD
	Cooling Method		Water
	Power Rating ISO 3046/1	kW	32
	Injection		TBD
	Distribution		Turbocharged Intercooler
ALTERNATOR	Consumption 100%	L/h	TBD
	Consumption 75%	L/h	TBD
	Consumption 50%	L/h	TBD
	Consumption 25%	L/h	
	Brand		STAMFORD
	Model		PI 144 J
	Continuous Power	kVA	40
	Coupling	SAE	3-11,5"
	N° Phases		3+N
	Ingress Protection	IP	IP21
	Insulation Class		H



Email info@svensson-generators.be
Phone +32 13 29 05 45
Address Vroentestraat 3
3540 Herk-de-Stad
Website www.svensson-generators.be

Svensson Generators' equipment is compliant with all required regulations to acquire CE marking including but not limited to:

- 2006/42 / EC, Machine Safety
- 2006/95 / EC, Low voltage
- 2004/108 / EC, Electromagnetic

Compatibility

- 2000/14 / EC and 2005/88 / EC, Sound emissions from outdoor machines.
- EN12100, EN13857, EN60204

P.R.P. - ISO 8258 (PRIME POWER)

It is the maximum power available for a variable power cycle that can occur for an unlimited number of hours per year between the marked maintenance intervals.


Consumable average power over a 24-hour period should not exceed 80% of P.R. 10% overload is only allowed for regulation purposes.

L.T.P. - ISO 3046 (LIMIT TIME POWER)

It is the maximum power available for use in variable loads for a limited number of hours per year (500 hours) within the following maximum operating limits: 100% load 25h / year - 90% load 200h / year. There is no overhead. It is applicable in case of interruption of distribution in zones of reliable electrical network.

Dimensions

Length (C)	Width (L)	Height (A)	Weight
2200 mm	900 mm	1375 mm	1000 Kg



Display

	MANUAL (MAN)	AUTOMATIC (AMF)		SYNC
Model	DSE 4510	DSE 6020MKII	DSE 7320	DSE 8610
Start/Stop Button	✓	✓	✓	✓
Remote Start/Stop*	✓	✓	✓	✓
Emergency Button	✓	✓	✓	✓
Hours Counter	✓	✓	✓	✓
Start/Stop Scheduler	✓	✓	✓	✓
Maintenance Scheduler	✓	✓	✓	✓
Engine Protection	✓	✓	✓	✓
Alternator Protection	✓	✓	✓	✓
Frequency	✓	✓	✓	✓
Engine RPM	✓	✓	✓	✓
Fuel Level %	✓	✓	✓	✓
Events Log	✓	✓	✓	✓
ATS Control	-	✓	✓	✓
Fuel Consumption l/h	-	-	✓	✓
Phases Sequence	-	-	✓	✓
ModBus Protocol	-	-	✓	✓
Synchronize - Parallel	-	-	✓	✓
Configurable DC outputs	4	4	6	8
Configurable Inputs	4	6	8	12

The technical characteristics described in this catalog corresponds to the information available at the time of printing. Svensson Generators is a trademark of Svensson Machinery BV.